

# Product overzicht

Aperçu des produits |  
Product overview |  
Produktübersicht

	<b>Frame</b>	<b>Max length wood logs</b>	<b>Interior</b>	<b>Weight</b>	<b>Output</b>	<b>Gas flue outlet</b>	<b>Air supply</b>	<b>Convection casing</b>	<b>Convection fan system</b>	<b>Extended adjustable legs</b>	<b>Opti-Air system</b>	<b>Standard</b>	<b>Flamme Verte</b>	<b>Flamme Verte Indice I'</b>	<b>1.BImSchV</b>	<b>Ecodesign 2022</b>	<b>Smoke Control Areas</b>	<b>CO (vol%)</b>	<b>energy efficiency class</b>
	frameless classic frame built-in frame 4-sided frame	max. cm.	ceramic concrete cast iron	kg, approx.	kW	Ø (mm.)	Ø (mm.)	standard	optional system	optional system	optional system	Flamme Verte	Flamme Verte Indice I'	1.BImSchV	Ecodesign 2022	Smoke Control Areas	CO (vol%)	energy efficiency class	
<b>Fronthaarden</b>																			
Evo-7 50-40		30		210	7-10	180	125					★★★★★★	0,50				0,1	A	
Evo-7 65-40		50		260	10-15	180	125					★★★★★★	0,40				0,1	A	
<b>Evo-7 Compact 55-45*</b>																			
Cuatro-7 50		30		150	7-10	180	125					★★★★★★	0,50				0,09	A	
Cuatro-7 60		30		170	7-11	180	125					★★★★★★	0,40				0,1	A	
Cuatro-7 75		50		200	10-15	180	125					★★★★★★	0,50				0,1	A	
<b>Cuatro-7 Compact 55*</b>																			
<b>Cuatro-7 Compact 70*</b>																			
Universal 65		35		112	6-9	150	125					★★★★★★	0,40				0,07	A	
Universal 70		40		115	7-10	180	125					★★★★★★	0,50				0,09	A	
Universal 75		40		126	7-11	180	125					★★★★★★	0,50				0,09	A	
Universal 80		40		128	8-12	180	125					★★★★★★	0,40				0,12	A	
Universal 85		50		141	8-12	180	125					★★★★★★	0,50				0,1	A	
Unilux 40		20		69	4-6	130	80					★★★★★★	0,50				0,08	A	
Unilux 45		20		87	5-7	130	80					★★★★★★	0,40				0,09	A	
Unilux 52		30		79	5-8	130	80					★★★★★★	0,40				0,06	A	
Unilux 55		30		93	6-9	130	80					★★★★★★	0,40				0,05	A	
Unilux 65		40		90	7-9	150	125					★★★★★★	0,60				0,08	A	
Unilux 67		40		109	7-10	150	125					★★★★★★	0,40				0,07	A	
Unilux 70		45		105	8-12	150	125					★★★★★★	0,40				0,07	A	
Unilux 75		50		107	9-13	150	125					★★★★★★	0,50				0,06	A	
Unilux 80		50		123	8-11	150	125					★★★★★★	0,40				0,09	A	
<b>Tweezijdige haarden</b>																			
Unilux 265 links / rechts		40		114	7-9	150	125					★★★★★★	0,60				0,1	A	
Unilux 270 links / rechts		45		138	9-12	180	125					★★★★★★	0,40				0,09	A	
<b>Driezijdige haarden</b>																			
Unilux 265 three sided		40		112	7-9	150	125					★★★★★★	0,60				0,1	A	
Unilux 270 three sided		45		135	9-12	180	125					★★★★★★	0,40				0,09	A	

\* beschikbaar vanaf Q1 2024  
disponible à partir du 1er trimestre 2024  
available from Q1 2024  
verfügbar ab Q1 2024